

	Standard E2-3RVX Options	Options
Load Capacity on 24" load center	5,000 lb	
Engine	Kubota® V2203 Diesel	
Horsepower	50 HP	
Driven Wheels	3	
Anti Stall Hydraulic Control	Yes	
Front Tires	10"x16.5", pneumatic (30")	Sand Tire
Rear Tire	31"x15.5", pneumatic	Sand Tire
Sealed Tires	Standard	
Speed	5.6 mph	
Gradeability	Standard Direction: 45% 4 Way Direction: 30%	
Turning Radius	90" regular	63" 4 Way
Weight*	6,424 lb	
Lift Height	144"	86"/120"
Tilt Forward/Back	7.5/6.5°	
Side Shift	8"	
Height, mast lowered	110"	88"/97"
Reach	Scissors Reach	
Fork Warning System	Yes	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Certified Roll Over Protection	Yes	
Hydraulic Support Arms	Yes	
Mounting System	EZ Hitch/EZ Mount/Moffett Mount	
Overall Width	100"	
Cargo Bay Width	63"	63"
Overall Length	118" regular	113" 4-Way
Overhang	74"	
Length under Truck	36"	
Ground Clearance	15"	
Warranty	1 year	24/36/48/60 mo.

* Weight, includes mast, forks, full size tires & fluids