

	<b>PB50</b>	<b>Options</b>
Load Capacity @ 24' load center	5,000 lb	5,500 lb
Engine - Diesel	CAT®, 4 cylinder	CAT®, 4 cylinder, Turbo
Horsepower	52 HP	62 HP
Driven Wheels	3	
Anti Stall Hydraulic Control	Yes	
Brakes	Dual, Front	
Tires	31"x15.5", pneumatic	Sand Tire
Sealed Tires	Yes	
Speed	8mph	
Gradeability	50+%	
Turning Radius	78"	
Weight *	5,890 lb	(PB55) 6,250 lb
Lift Height	86"	120"/144"/154"/165"
Tilt Forward/Back	8°/8° (After 4/2003)	
Side Shift	8"	
Height, mast lowered	96"	101"/110"/118"/110"
Reach	Moving Mast	Double Reach
Seat Belt Interlock	Yes	
Certified Roll Over Protection	Yes	Weather Shield
Support Arms	No	Yes
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	100"	
Cargo Bay Width	59"	
Overall Length	131"	
Overhang	80"	
Length under Truck	23"	
Ground Clearance	15"	
Warranty	1 year	24/36 months

\* Weight, includes mast, forks, full size tires & fluids

CAT® is a registered trademark of Caterpillar, Inc.